# Notes de bas de page en mode multi-colonne*

Frank Mittelbach
Electronic Data Systems (Deutschland) GmbH
Eisenstraße 56 N15
D-6090 Rüsselsheim

Traduction française par Jean-Pierre Drucbert†

31 octobre 2001

## 1 Préface à la version 1.1

Cette nouvelle version est globalement inchangée par rapport à la précédente. J'ai modifié les macros pour qu'elles fonctionnent avec LaTeX 2ε et utilisé quelques-unes de ses facilités. Par exemple, la commande `\preparefootins` est maintenant appelée automatiquement au `\begin{document}`, permettant ainsi à l'utilisateur d'ajuster la longueur `\textheight` dans le préambule.

Il n'est pas étonnant que j'ai été obligé de modifier certaines macros parce qu'elles utilisaient des routines d'affichage de LaTeX de très bas niveau. Heureusement, cela n'est pas nécessaire pour la plupart des packages quand on veut les mettre à jour pour utiliser la syntaxe de LaTeX 2ε.

J'ai aussi mis à jour la documentation pour la rendre conforme à la terminologie de LaTeX 2ε ; par exemple, ceci est un « package » puisque les classes de document n'auront pas à se soucier de lui. Cependant, il est fort probable que j'ai oublié des corrections.

## 2 Introduction

Le positionnement des notes dans une mise en page sur plusieurs colonnes a toujours été un souci pour moi. L'approche prise par LaTeX (c'est-à-dire placer les notes séparément en dessous de chaque colonne) peut être parfaite s'il n'y a à peu près aucune note. Mais le résultat peut sembler maladroit si les deux colonnes contiennent des notes, en particulier si elles occupent un espace différent.

Dans le package `multicol` [5], j'utilise des notes en bas de page sur toute la largeur de la page, mais là encore le résultat n'est pas très agréable à l'œil car des notes courtes provoquent des vides blancs indésirables. Bien sûr, l'objectif principal de ce package était d'avoir un algorithme d'équilibrage des colonnes permettant de changer le nombre de colonnes sur la même page. Avec cette possibilité, la place naturelle des notes semblait être le bas de la page [1] mais en regardant le résultat il semble préférable d'éviter complètement les notes dans une telle mise en page.

Une autre possibilité est de transformer les notes de bas de page en notes finales, c'est-à-dire de les imprimer à la fin de chaque chapitre ou à la fin de l'ensemble du document. Mais je suppose que chaque personne qui a un jour lu un livre ainsi réalisé [2] sera de mon avis : il est pénible de chercher les notes en fin d'ouvrage et de revenir au texte, en un va-et-vient incessant, si bien que le lecteur est tenté d'ignorer

*Le package LaTeX `ftnright.sty` qui est décrit ici a le numéro de version ? en date du ?.

†Dernière mise à jour le 29/01/2000

1. Vous ne pouvez pas utilisez des notes par colonne en bas de page, puisque le nombre de colonnes peut changer dans la page.

2. En particulier les livres écrits par des historiens ou des philosophes.

complètement les notes finales.

Quand j'ai écrit l'article sur « Les extensions futures de TEX » [6], j'étais de nouveau peu satisfait de l'aspect des notes, et puisque cet article devait montrer certains aspects de la typographie de haute qualité, j'ai décidé de m'attaquer au problème des notes en bas de page en modifiant la routine de sortie de LATEX dans ce but. La mise en page utilisée était inspirée du l'almanach de la Gutenberg Gesellschaft Mainz [2]. Plus tard, j'ai vu qu'elle était aussi recommandée par Jan White [9]. Pour la mise en page des notes, j'ai aussi consulté les ouvrages de Jan Tschichold [8] et Manfred Simoneit [7], que je recommande à quiconque lisant l'allemand.

### 2.0.1 Nouvelle mise en page

Le résultat de ce travail est présenté ici et le lecteur peut juger par lui-même de sa réussite ou de son échec[3]. L'idée principale de cette mise en page est de rassembler les notes de toutes les colonnes d'une page et de les placer toutes ensemble en bas de la colonne de droite. En permettant suffisamment d'espace entre les notes et le texte et, de plus, en composant les notes dans des caractères plus petits[4], j'ai décidé qu'il était possible de supprimer le trait habituel de séparation entre le texte et les notes qui est d'ordinaire utilisé par la plupart des publications réalisées avec TEX[5]. De plus, j'ai décidé que les numéros de notes[6] seront sur la ligne de base et non plus surélevés comme des exposants[7].

Finalement ceci semble donner une bonne mise en page et, ce qui est assez surprenant, les modifications nécessaires sur la routine de sortie de LATEX furent néanmoins étonnamment simples.

### 2.0.2 Utilisation

Ce package peut (théoriquement) être utilisé avec tout autre package de LATEX qui ne modifie pas les trois éléments internes qu'elle modifie déjà[8]. Dans la plupart des cas, il est préférable de charger ce package en dernier dans le préambule pour s'assurer que les paramètres ne sont pas modifiés par d'autres packages.

Il est dommage que le LATEX actuel ne permette pas de faire ces changements sans modifier les routines internes de LATEX. Pour le futur LATEX3, nous ajouterons certainement la possibilité de faire de tels changements plus facilement.

# 3 Le générateur de documentation

La première partie du code contient le fichier TEX générant la documentation, c'est-à-dire le document que vous êtes en train de lire. Il est extrait de ce fichier par le programme `docstrip`. Si vous ne voulez faire aucun changement dans cette documentation, vous pouvez lancer LATEX $2_\varepsilon$ directement sur le fichier `.dtx` pour obtenir la documentation.

```
1 ⟨*driver⟩
2 \documentclass[twocolumn]{article}
3
4 \usepackage{ftnright}
5 \usepackage{doc}
```

3. Notez que ce package ne fait que modifier l'emplacement des notes. Comme cette documentation utilise le package `doc` [1], qui affiche des nombres en police minuscule pour visualiser les numéros de lignes du code source, le rendu général n'est pas parfait. Ce package fait maintenant partie intégrante de LATEX $2_\varepsilon$.

4. La mise en page pour *TUGboat* utilise la même taille de caractères pour les notes et le texte, ce qui donne, à mon avis, trop d'importance aux notes.

5. Il est possible de rétablir ce trait, en redéfinissant la commande `\footnoterule` [3, p. 156], mais il faut noter que cette commande ne doit occuper aucun espace vertical, il faut donc avoir recours à un espacement négatif pour compenser l'épaisseur du trait.

6. Les petits numéros ou symboles, par exemple le « 6 » au début de cette note.

7. Bien sûr, ceci n'est fait que pour la marque qui précède le texte de la note et non pour celle servant d'appel de note dans le texte principal, où un numéro ou un symbole surélevé en petits caractères permet de garder le fil du texte, sans interruption.

8. Ce sont les macros `\@startcolumn`, `\@makecol` et `\@outputdblcol` comme nous le verrons ci-dessous. Bien sûr, ce package n'a d'effet qu'avec une mise en page sur deux colonnes (comme `ltugboat`) due à la classe du document, à une option de classe `twocolumn`, ou après une commande `\twocolumn`.

```
6 ⟨/driver⟩

7 ⟨*driver⟩
8 \AtBeginDocument{\MakeShortVerb{\|}}
9
10 \newcommand{\TUB}{{\sl TUGboat\/}}
11 \renewcommand\DescribeMacro[1]{\fbox
12           {\PrintDescribeMacro{#1}}}
13 \renewcommand\DescribeEnv[1]{\fbox
14           {\PrintDescribeEnv{#1}}}
15 \renewcommand\PrintMacroName[1]{}
16
17 \setlength{\parindent}{1em}
18 \setlength{\parskip}
19           {2pt plus1pt minus1pt}
20 \setlength{\headsep}{20pt}
21 \setlength{\columnsep}{1.5pc}
22 \renewcommand{\bottomfraction}{.4}
23
24 \flushbottom
25 \CodelineIndex
26 \RecordChanges      % produce history
27 \EnableCrossrefs
28
29 \setcounter{IndexColumns}{2}
30 \IndexPrologue{\section{Index}
31  Les numéros représentent les ligne
32  du code source où l'entrée apparait,
33  en soulignement lorsqu'il s'agit de
34  sa définition.}
35
36 \begin{document}
37   \DocInput{f-ftnright.dtx}
38 \end{document}
39 ⟨/driver⟩
```

# 4 The Implementation

As usual, we start by identifying the current version of this package file in the transcript file.[9] This actually happens at the very top of this file so it is commented out here.

```
\ProvidesPackage{ftnright}[\filedate\space
              LaTeX2e package \fileversion]
```

To implement the layout described, above we have to distinguish between the left and the right column on a page. For this purpose LaTeX maintains the switch `\if@firstcolumn`. When assembling material for the left (i.e., the first) column, footnotes should take up no space, since they are held over for the second column. In the second column these footnotes are combined with the ones found there and placed a suitable distance from the main text at the bottom of this column.

This means that we have to change certain parameters for the insertion `\footins` when we construct the second column. The right place to do this is in the LaTeX macro `\@outputdblcol` which we are going to change later on. What settings for the insertion parameters are appropriate? For setting the first column `\count\footins` and `\skip\footins` should both be zero since footnotes are held over while for the second column `\count\footins` should be 1000 and the `\skip\footins` has to be set to the desired separation between main text and footnotes.[10]

We will allow one column of footnotes (i.e., the right column) at most, so that `\dimen\footins` has to equal `\textheight`. In principle, it would be possible to allow for even more footnotes, but this would complicate matters enormously.[11]

Since a document usually starts with a left column, we have to set `\count` and `\skip\footins` on top-

9. Nico Poppelier suggested omitting the `\typeout` statements in the production version of the files to avoid showing all that unnecessary information to the user. While I accept his criticism as valid, I decided that this information should at least be placed into the transcript file to make it easier to detect problems arising from the use of older versions. This happens now automatically as the command `\ProvidesPackage` will only write to the transcript file.

10. A value of 1000 means that there is a one-to-one relationship between the real size of the footnote and the size finally occupied by the footnote on the current page.

11. It is not possible to make `\dimen\footins` larger than `\textheight` directly, because this would result in a full left column (with text) and more than one column of footnotes. Instead, one has to make footnotes visible to the page generation algorithm again at the moment when a full column of footnotes is assembled, but we still have some space left in the first column. It is a nice enhancement, and, I suppose, it is of some value for preparing publications in certain disciplines, so here is the challenge ...

level to zero. For this purpose, we define a macro `\preparefootins` which will first save the current value of `\skip\footins` in a safe place. This saved value will be used later for the second column. In this way, it is possible for the user or a designer of a document class to adjust this parameter without fiddling with the code of this package file.

```
⟨*package⟩
\def\preparefootins{%
  \global\rcol@footinsskip\skip\footins
  \global\skip\footins\z@
  \global\count\footins\z@
```

We will also assign `\textheight` to `\dimen \footins` to allow the user to change this parameter in the preamble.

```
  \global\dimen\footins\textheight}
```

It is necessary to make the assignments above `\global` because we are going to use this macro in the output routine which has an implicit grouping level to keep the changes made by it local.

Of course, we have to allocate the `skip` register that we used above:

```
\newskip\rcol@footinsskip
```

Now we have all the necessary tools available to tackle `\@outputdblcol`. We have to remember that when `\if@firstcolumn` equals `\iftrue`, we are currently starting to build the second column, i.e., that the first column is already assembled. Therefore, the macro will start with the following code:

```
\def\@outputdblcol{\if@firstcolumn
  \global\@firstcolumnfalse
```

After changing the switch, we save the first column (which was placed by preceeding macros in `\@outputbox`) in the box register `\@leftcolumn`. Since we are inside the output routine, all those assignments have to be `\global` to take any effect.

```
  \global\setbox\@leftcolumn\box\@outputbox
```

Then, we make the footnotes visible to the page generation algorithm by setting `\count\footins` to 1000 (`\@m` is an abbreviation for this number) and `\skip\footins` to its saved value (i.e., `\rcol@footinsskip`).

```
  \global\count\footins\@m
  \global\skip\footins\rcol@footinsskip
```

We also have to reinsert all footnotes left over from the first column to make sure that they are reconsidered by the page generation algorithm of TEX using the new values for `\count` and `\skip\footins`. But this will be done later in the macro `\@startcolumn`.

If we have just finished the right column, i.e., when `\if@firstcolumn` equals `\iffalse`, we will reset the `\footins` parameters as explained above using the utitlity macro `\preparefootins`.

```
  \else \preparefootins
```

Then, we compose both columns in `\@outputbox`, combine them with all page-wide floats for this page (`\@combinedblfloats`), attach header and footer, and ship out the result (`\@outputpage`). Finally we look to see whether it is possible to generate following pages consisting only of page-wide floats.[12]

```
  \global\@firstcolumntrue
  \setbox\@outputbox\vbox{\hbox to\textwidth
    {\hbox to\columnwidth
                {\box\@leftcolumn\hss}%
     \hfil\vrule\@width\columnseprule\hfil
     \hbox to\columnwidth
                {\box\@outputbox\hss}}}%
  \@combinedblfloats\@outputpage
  \begingroup
   \@dblfloatplacement\@startdblcolumn
   \@whilesw\if@fcolmade\fi
    {\@outputpage\@startdblcolumn}%
  \endgroup
\fi}
```

There is a fundamental flaw in LATEX's output routine for float columns and float pages: split footnotes, i.e., footnotes which are only partly typeset on the preceding page are not resolved. They are held over until LATEX starts a page (or column) containing text besides floats again. For our current layout, this would mean, that if LATEX decided to make the right column of a page a float column, footnotes from the left column would appear on a

12. This part is copied directly from the original LATEX macro. Details about the used macros, their interfaces and meanings can be found in the LATEX $2_\varepsilon$ source code [4].

later page. A real cure for this problem would be to rewrite two-thirds of LaTeX's output routine, so I am leaving this open for the interested reader.

But the problem shows up even if only one float is contributed to the right column since LaTeX assumes that the whole column is usable, whereas some of it might actually be already devoted to footnotes from the left column. So we have to change the output routine at least in the part that contributes floats to the next column. The macro involved is called `\@startcolumn`. The first thing we do is to check and see whether any deferred floats exists.

```
\def\@startcolumn{%
  \ifx\@deferlist\@empty
```

If not, we set the switch `\if@fcolmade` to `false` which says that we did not succeed in making a float column. Then, we set `\@colroom` to `\@colht`. The register `\@colht` holds the amount of space that is available for floats, text, and footnotes in one column, i.e., it equals `\textheight` minus the space devoted to page-wide floats. `\@colroom` is a similar register which holds the value `\@colht` minus space for column floats that are already contributed to the current column. Of course, both values should be equal when we start a new column.

```
    \global\@fcolmadefalse
```

**Puzzle:**

Given a simple TeX document containing only straight text, is it possible for the editor, after deleting one sentence, to end up with a document producing an extra page?

We assume that the deleted text contains no TeX macros and that the document was prepared with a standard macro package like the one used for *TUGboat* production.

The answer will be given in the next issue.

```
    \global\@colroom\@colht
  \else
```

If there are floats waiting for a change to be processed, the situation is more difficult. In this case, we have to reduce both `\@colht` and `\@colroom` by the amount of space that will be needed for the footnotes from the left column. So we must check whether such footnotes are present. As we have not reinserted them in `\@outputdblcol`, we can check the `\footins` box.

```
    \ifvoid\footins\else
```

If there are some, we measure the space that will be occupied by them. This measurement is not really exact. If we have a full column of footnotes, it will be too high, but this does matter since we need it only for an upper bound on the free space available for floats.

```
      \ftn@amount\ht\footins
      \advance\ftn@amount\dp\footins
      \advance\ftn@amount\skip\footins
    \fi
```

We then reduce the `\@colht` by this amount and again assign `\@colroom` the value of `\@colht`. If no footnotes are present, we substract zero, so there is no harm in doing this operation all the time.

```
    \global\advance\@colht-\ftn@amount
    \global\@colroom\@colht
```

Now, we call another internal LaTeX macro that will try to contribute floats to the next column. It will use the register `\@colht` when trying to build up a float column, which is the reason for reducing this register. If it succeeds, it will set the switch `\if@fcolmade` to `true`, otherwise, to `false`. If no float column is possible, it will try to place some or all of the deferred floats to the top or the bottom of the next column, thereby, using and reducing the value of the register `\@colroom`.

```
    \@xstartcol
```

Afterwards, we have to restore the correct values for `\@colht` and `\@colroom` again, but this time, they may differ, so that we have to `\advance` both registers separately by `\ftn@amount`.

```
    \global\advance\@colht\ftn@amount
```

```
    \global\advance\@colroom\ftn@amount
  \fi
```

Now, after doing the things depending on the status of the `\@deferlist`, we have to incorporate the left over footnotes in the new column. First we check whether a float column was produced by `\@xstartcol` or not.

```
  \if@fcolmade
```

If so, we do something awful. To make use of the `\@makecol` macro, which attaches footnotes to `\box` 255 and places the result in the box register `\@outputbox`, we have to assign `\@outputbox` (i.e., the result of `\@xstartcol`) to `\box` 255.[13]

```
    \setbox\@cclv\box\@outputbox
    \@makecol
  \else
```

If no float column was produced, we reinsert the held over footnotes so that they can be reconsidered by the page generation algorithm of TEX. But it is necessary to ensure that this operation is done only when footnotes are actually present.[14]

```
    \ifvoid\footins\else
      \insert\footins{\unvbox\footins}\fi
  \fi}
```

Of course, we also have to allocate the dimen register. It will be automatically initialized to zero.

```
\newdimen\ftn@amount
```

The macro `\@xtsartcol` was removed in LATEX $2_\varepsilon$ but we introduce it here again for the moment.

```
\def\@xstartcol{%
  \@tryfcolumn \@deferlist
  \if@fcolmade
  \else
    \begingroup
      \let \@tempb \@deferlist
      \global \let \@deferlist \@empty
      \let \@elt \@scolelt
      \@tempb
    \endgroup
  \fi
}
```

The other internal macro that we have to change is `\@makecol`, a macro that is called whenever one column of material is assembled and column floats and footnotes have to be added. Again, we have to distinguish between actions for the first and the second column.

```
\def\@makecol{\if@firstcolumn
```

For the first column, we leave the footnotes in their box and simply save the contents of box 255 in the `\box` register `\@outputbox`.

```
  \setbox\@outputbox\box\@cclv
```

But if the user errously forgot to specify a twocolumn layout, we will always typeset the first column, so that the footnotes are never printed. Therefore we better check for this special case and output the footnotes on a separate page in an emergency.[15]

```
  \if@twocolumn \else
    \ifvoid\footins \else
      \@latexerr{ftnright package
                 used in one-column mode}%
   {The ftnright package was designed to
    work with LaTeX's standard^^Jtwocolumn
    option. It does *not* work with the
    multicol package.^^JSo please specify
    'twocolum' in the
    \noexpand\documentclass command.}%
      \shipout\box\footins \fi\fi
\else
```

When we construct the second column, we must first check whether footnotes are actually present. If not, we perform the same actions as before.

```
  \ifvoid\footins
    \setbox\@outputbox\box\@cclv
  \else
```

13. In German, we call this "from the back through the chest into the eyes".

14. Otherwise, we might get an undesired extra vertical space coming from `\skip\footins`, even if there are no footnotes on the page.

15. Otherwise, the footnotes are held over for ever, preventing TEX from finishing the document successfully. Instead, TEX will produce infinity many empty pages at the end of the document, trying in vain to output the held over footnotes. This problem was found by Rainer Schöpf when we prepared the paper for the Cork conference.

But, if footnotes are present, it may be possible that the whole column consists of footnotes, i.e., `\box` 255 is empty. In this case, there is no use in placing any glue (`\skip\footins`) in front,[16] so we have to check for this possibility.

```
    \setbox\@outputbox\vbox
      {\ifvoid\@cclv \else
         \unvbox\@cclv
         \vskip\skip\footins\fi
```

But in any case, we place the `\footnoterule` in front of the footnotes even if this macro is not used by this package.[17] This ends the if-statement testing whether footnotes are present or not. It also ends the code which differs depending on the column number.

```
         \color@begingroup
         \normalcolor
         \footnoterule\unvbox\footins
         \color@endgroup}\fi
  \fi
```

Now the column floats are added at the top and the bottom, and the `\@outputbox` is adjusted to the full column height so that the glue inside will stretch in certain situations.[18] Again, this code is copied verbatim from the original source, so I won't dwell on details.[19][20]

```
  \xdef\@freelist{\@freelist\@midlist}%
  \global \let \@midlist \@empty
  \@combinefloats
  \ifvbox\@kludgeins
    \@makespecialcolbox
  \else
   \setbox\@outputbox\vbox to\@colht
     {\boxmaxdepth\maxdepth
      \@texttop
      \@tempdima\dp\@outputbox
      \unvbox\@outputbox
      \vskip-\@tempdima
      \@textbottom}%
  \fi
  \global\maxdepth\@maxdepth}
```

Now we can tackle the remaining small changes to the standard layout. I decided to use a smaller size for footnotes but with a slightly larger leading than usual. This means that we have to redefine the `\footnotesize` macro which depends on options like `11pt` etc. Fortunately, there is a simple way to find out the main size of the document: the macro `\@ptsize` contains 0, 1, or 2 standing for 10, 11, or 12 points document text size.[21]

```
\ifcase \@ptsize
\renewcommand\footnotesize{%
 \@setfontsize\footnotesize\@viiipt{9.9}%
 \abovedisplayskip 6\p@\@plus2\p@\@minus4\p@
 \abovedisplayshortskip \z@ \@plus\p@
 \belowdisplayshortskip
                    3\p@\@plus\p@\@minus2\p@
 \def\@listi{\leftmargin\leftmargini
          \topsep 3\p@ \@plus\p@ \@minus\p@
          \parsep 2\p@ \@plus\p@ \@minus\p@
          \itemsep \parsep}%
 \belowdisplayskip \abovedisplayskip
```

16. In fact, it would be a mistake since this glue was not taken into account when the footnotes where assembled, so it would produce an overfull box.

17. This decision is certainly open to criticism, since there is nothing to separate. On the other hand, a rule or some other ornament in front of the footnotes is part of the design which should be used concistently throughout a document. As a last argument in favor of the rule, consider the situation where LaTeX decided to place only floats and footnotes into the right hand column. In this case a separator again seems adequate. In this situation one can even argue that it is necessary to put in the `\skip\footins`.

18. It is an interesting question as to whether the current layout works well with bottom floats or not. Actually, I would prefer to place the footnotes below the bottom floats instead of above, as it is done here. At least when the floats are part of the document and not puzzles thrown in. But I was too lazy to implement it because I seldom use floats. If somebody implements this layout (some parts of this macro have to be changed) I would be interested in seeing the code and some sample results.

19. I only changed `\dimen128` into `\@tempdima` which is, besides being faster and shorter, only a cosmetic change. The use of this hardwired dimen register seems to indicate that this part of LaTeX was written very early and left unchanged since then: an interesting fact for software archeologists.

20. For the LaTeX $2_\varepsilon$ upgrade I had to add the support for the `\enlargethispage` command—let's hope I did it in the correct way.

21. In the new release I used the definitions from the class option files `size1?.clo` and modified them slightly. In the previous release there was no correction for the list parameters etc., thus giving you incorrect spacing if somebody used display lists in footnotes.

```
}
\or
\renewcommand\footnotesize{%
 \@setfontsize\footnotesize\@ixpt{11.1}%
 \abovedisplayskip 8\p@\@plus2\p@\@minus4\p@
 \abovedisplayshortskip \z@ \@plus\p@
 \belowdisplayshortskip
                4\p@ \@plus2\p@ \@minus2\p@
 \def\@listi{\leftmargin\leftmargini
         \topsep 4\p@ \@plus2\p@\@minus2\p@
         \parsep 2\p@ \@plus\p@ \@minus\p@
         \itemsep \parsep}%
 \belowdisplayskip \abovedisplayskip
}
\or
\renewcommand\footnotesize{%
 \@setfontsize\footnotesize\@xpt{12.3}%
 \abovedisplayskip10\p@\@plus2\p@\@minus5\p@
 \abovedisplayshortskip \z@ \@plus3\p@
 \belowdisplayshortskip
                6\p@ \@plus3\p@ \@minus3\p@
 \def\@listi{\leftmargin\leftmargini
        \topsep 6\p@ \@plus2\p@ \@minus2\p@
        \parsep 3\p@ \@plus2\p@ \@minus\p@
        \itemsep \parsep}%
 \belowdisplayskip \abovedisplayskip
}
\fi
```

Setting footnotes in smaller type and separating them with sufficiant space from the main text allow us to omit the `\footnoterule` normally used.

```
\let\footnoterule\@empty
```

Individual footnotes are separated from each other by a more or less baseline skip of the text size. This can be specified with the following code:

```
\AtBeginDocument
  {\global\footnotesep\ht\strutbox}
```

The use of the LaTeX $2_\varepsilon$ hook `\AtBeginDocument` is a big help since it allows us to defer everything that might depend on user setting inside the preamble to the `\begin{document}` environment start.

And finally, a small but nice change, to the mark at the beginning of the footnote text. We will place it at the baseline instead of raising it as a superscript. Additionally, it will get a dot as punctuation.

```
\long\def\@makefntext#1{\parindent 1em
  \noindent\hbox to 2em{}%
  \llap{$\@thefnmark.\;\;$}#1}
```

# 5 Initialisation

We defined the macro `\preparefootins` above, but we also have to use it to prepare typesetting the first column. As a default for the separation of footnotes and text on the second column, we use the following:

```
\setlength{\skip\footins}
          {10pt plus 5pt minus 3pt}
\AtBeginDocument{\preparefootins}
```
⟨/package⟩

Of course, this value can be changed by the user as described in the introduction.

# References


[1] M. Goossens, F. Mittelbach et A. Samarin. The LaTeX Companion. Addison-Wesley, Reading, Massachusetts, 1994.

[2] Hans-Joachim Koppitz, editor. *Gutenberg Jahrbuch.* Gutenberg-Gesellschaft, Mainz.

[3] Leslie Lamport. *LaTeX: A Document Preparation System.* Addison-Wesley, Reading, Massachusetts, 1986.

[4] LaTeX3 project. LaTeX $2_\varepsilon$ distribution, 1994. Souces for LaTeX $2_\varepsilon$ the successor to LaTeX 2.09.

[5] Frank Mittelbach An environment for multi-column output. *TUGboat*, 10(3):407–415, November 1989.

[6] Frank Mittelbach E-TeX: Guidelines to future TeX extensions. In Lincoln K. Durst, editor, *TUGboat*, 11(3): *1990 TUG Annual Meeting Proceedings*, pages 337–345, September 1990.

[7] Manfred Siemoneit. *Typographisches Gestalten.* Polygraph Verlag, Frankfurt am Main, second edition, 1989.

[8] Jan Tschichold. *Ausgewählte Aufsätze über Fragen der Gestalt des Buches.* Birkhäuser Verlag, Basel, 1987. Second printing.

[9] Jan White. *Graphic Design for the Electronic Age.* Watson Guptill, Xerox Press, New York, 1988.

# 6 Index

Les numéros représentent les ligne du code source où l'entrée apparait, en soulignement lorsqu'il s'agit de sa définition.

### Symbols


\/ . . . . . 10
\; . . . . . 189
\@cclv . . . . . 84, 104, 118, 121, 122
\@colht . . . . . 70, 77, 78, 80, 135
\@colroom . . . . . 70, 78, 81
\@elt . . . . . 98
\@fcolmadefalse . . . . . 69
\@firstcolumnfalse . . . . . 48
\@firstcolumntrue . . . . . 53
\@kludgeins . . . . . 132
\@latexerr . . . . . 107
\@leftcolumn . . . . . 49, 56
\@listi . . . . . 151, 164, 177
\@m . . . . . 50
\@makecol . . . . . 85, 103
\@makefntext . . . . . 187
\@makespecialcolbox . . . . . 133
\@maxdepth . . . . . 143
\@minus . . . . . 147, 150, 152, 153, 160, 163, 165, 166, 173, 176, 178, 179
\@outputbox 49, 54, 59, 84, 104, 118, 120, 135, 138, 139
\@outputdblcol . . . . . 47
\@outputpage . . . . . 60, 64
\@plus . . . . . 147, 148, 150, 152, 153, 160, 161, 163, 165, 166, 173, 174, 176, 178, 179
\@scolelt . . . . . 98
\@setfontsize . . . . . 146, 159, 172
\@startcolumn . . . . . 67
\@startdblcolumn . . . . . 62, 64
\@tempb . . . . . 96, 99
\@thefnmark . . . . . 189
\@tryfcolumn . . . . . 92
\@xstartcol . . . . . 79, 91
\| . . . . . 8


### A


\abovedisplayshortskip . . . . . 148, 161, 174
\abovedisplayskip . . . 147, 155, 160, 168, 173, 181
\AtBeginDocument . . . . . 8, 185, 192


### B


\begin . . . . . 36
\belowdisplayshortskip . . . . . 149, 162, 175
\belowdisplayskip . . . . . 155, 168, 181
\bottomfraction . . . . . 22
\boxmaxdepth . . . . . 136


### C


\CodelineIndex . . . . . 25
\color@begingroup . . . . . 124
\color@endgroup . . . . . 127
\columnsep . . . . . 21
\columnseprule . . . . . 57
\columnwidth . . . . . 55, 58


### D


\DescribeEnv . . . . . 13
\DescribeMacro . . . . . 11
\DocInput . . . . . 37
\documentclass . . . . . 2, 114


### E


\EnableCrossrefs . . . . . 27
\end . . . . . 38


### F


\fbox . . . . . 11, 13
\flushbottom . . . . . 24
\footins . . . . . 42–45, 50, 51, 72–75, 87, 88, 106, 115, 117, 123, 126, 190
\footnoterule . . . . . 126, 184
\footnotesep . . . . . 185
\footnotesize . . . . . 144
\ftn@amount . . . . . 73–75, 77, 80, 81, 90


### H


\headsep . . . . . 20


### I


\if@fcolmade . . . . . 63, 83, 93
\if@firstcolumn . . . . . 47, 103
\if@twocolumn . . . . . 105
\ifvbox . . . . . 132
\ifvoid . . . . . 72, 87, 106, 117, 121
\IndexPrologue . . . . . 30
\insert . . . . . 88
\itemsep . . . . . 154, 167, 180


### L


\leftmargin . . . . . 151, 164, 177

\leftmargini . . . . . 151, 164, 177

M

\MakeShortVerb . . . . . 8
\maxdepth . . . . . 136, 143

N

\newcommand . . . . . 10
\newdimen . . . . . 90
\newskip . . . . . 46
\noexpand . . . . . 114
\normalcolor . . . . . 125

P

\p@ . . . . . 147, 148, 150, 152, 153, 160, 161, 163, 165, 166, 173, 174, 176, 178, 179
\parindent . . . . . 17, 187
\parsep . . . . . 153, 154, 166, 167, 179, 180
\parskip . . . . . 18
\preparefootins . . . . . 40, 52, 192
\PrintDescribeEnv . . . . . 14
\PrintDescribeMacro . . . . . 12
\PrintMacroName . . . . . 15

R

\rcol@footinsskip . . . . . 42, 46, 51
\RecordChanges . . . . . 26
\renewcommand . . . . . 11, 13, 15, 22, 145, 158, 171

S

\saved@footinsskip . . . . . 40
\section . . . . . 30
\setcounter . . . . . 29
\setlength . . . . . 17, 18, 20, 21, 190
\shipout . . . . . 115
\sl . . . . . 10
\strutbox . . . . . 186

T

\textheight . . . . . 45
\textwidth . . . . . 54
\topsep . . . . . 152, 165, 178
\TUB . . . . . 10

U

\usepackage . . . . . 4, 5

# Change History

v1.0b
\@startcolumn: Macro added to correct float problems . . . . . 4
v1.0c
\@makecol: Introduced crude recovery if twocolumn false. . . . . 6
\@makefntext: Added dot as recommended by Tschichold. . . . . 8
v1.0d
\@makecol: Better help message . . . . . 6
General: Ajout du générateur de documentation dans le source . . . . . 2
v1.0e
General: Ajout de l'historique des changements . 2
v1.1a
\@makecol: Upgrades for LaTeX2e . . . . . 7
\@xstartcol: Macro reintroduced . . . . . 6
General: Mis à jour pour LaTeX2e . . . . . 1
\footnotesep: Upgrades for LaTeX2e . . . . . 8
\footnotesize: Upgrades for LaTeX2e . . . . . 7
v1.1b
General: Driver mis en avant . . . . . 1
v1.1c
General: Utilise article.cls pour la documentation . . . . . 1
v1.1d
\@makecol: Added the color@group macros and \normalcolor to make this colorsafe . . . . . 7