Le package hhline*

David Carlisle
carlisle@cs.man.ac.uk

Traduit de l'anglais par:
Jean-Pierre Drucbert

1994/05/23

Abstract

Ce package étend les possibilités de lignes horizontales et verticales dans un environnement `array` ou `tabular`. Il introduit la nouvelle commande `\hhline` qui produit une ligne comme `\hline` ou une double ligne comme `\hline\hline`, sauf pour leur interaction avec les lignes verticales.

1 Introduction

L'argument de `\hhline` est similaire au préambule d'un environnement `array` ou `tabular`. Il consiste en une liste d'éléments (tokens) ayant les significations suivantes:

- `=` Une double hline sur la largeur d'une colonne.
- `-` Une simple hline sur la largeur d'une colonne.
- `~` Une colonne sans hline.
- `|` Une vline qui 'coupe' une hline simple ou double.
- `:` Une vline qui est brisée par une double hline.
- `#` Un double segment hline entre deux vlines.
- `t` La moitié supérieure d'un double segment hline.
- `b` La moitié inférieure d'un double segment hline.
- `*` `*{3}{==#}` s'expanse en `==#==#==#`, comme dans la `*`-forme pour le préambule.

Si une double vline est spécifiée (`||` ou `::`) alors les hlines produites par `\hhline` sont brisées. Pour obtenir l'effet d'une hline 'passant à travers' la double vline, utilisez un `#` ou omettez les spécificateurs de vline, selon que vous vouliez ou non que la double vline soit brisée.

Les tokens `t` et `b` doivent être utilisés entre deux traits verticaux. `|tb|` produit les mêmes lignes que `#`, mais est moins efficace. L'utilisation principale pour ceci est de faire des constructions telles que `|t:` (coin supérieur gauche) et `:b|` (coin inférieur droit).

Si `\hhline` est utilisée pour faire une simple hline, alors l'argument ne doit contenir que des tokens `-`, `~` et `|` (et des `*`-expressions).

*Ce fichier a le numéro de version v2.03, dernière mise à jour le 1994/05/23.

Voici un exemple utilisant la plupart de ces possibilités:

```
\begin{tabular}{||cc||c|c||}
\hhline{|t:==:t:==:t|}
a&b&c&d\\
\hhline{|:==:|~|~||}
1&2&3&4\\
\hhline{#==#~|=#}
i&j&k&l\\
\hhline{||--||--||}
w&x&y&z\\
\hhline{|b:==:b:==:b|}
\end{tabular}
```

a	b	c	d
1	2	3	4
i	j	k	l
w	x	y	z

Les lignes produites par la commande `\hline` de LaTeX sont formées d'une seule primitive `\hrule` de TeX. Les lignes produites par `\hhline` sont faites d'une quantité de petits segments de ligne. TeX les placera très précisément dans le fichier `.dvi`, mais le programme que vous utilisez pour imprimer le fichier `.dvi` peut ne pas les aligner exactement. (Un problème similaire peut survenir avec les lignes obliques dans l'environnement `picture`).

Si ceci pose un problème, vous pouvez soit essayer un autre programme d'impression, si cela est possible, ou alors augmenter `\arrayrulewidth` pour essayer d'en réduire les effets.

2 Les macros (section non traduite)

```
⟨*package⟩
```

`\HH@box` Makes a box containing a double hline segment. The most common case, both rules of length `\doublerulesep` will be stored in `\box1`, this is not initialised until `\hhline` is called as the user may change the parameters `\doublerulesep` and `\arrayrulewidth`. The two arguments to `\HH@box` are the widths (ie lengths) of the top and bottom rules.

```
\def\HH@box#1#2{\vbox{%
  \hrule \@height \arrayrulewidth \@width #1
  \vskip \doublerulesep
  \hrule \@height \arrayrulewidth \@width #2}}
```

`\HH@add` Build up the preamble in the register `\toks@`.

```
\def\HH@add#1{\toks@\expandafter{\the\toks@#1}}
```

`\HH@xexpast` `\HH@xexnoop` We 'borrow' the version of `\@xexpast` from Mittelbach's array.sty, as this allows `#` to appear in the argument list.

```
\def\HH@xexpast#1*#2#3#4\@@{%
   \@tempcnta #2
   \toks@={#1}\@temptokena={#3}%
   \let\the@toksz\relax \let\the@toks\relax
   \def\@tempa{\the@toksz}%
   \ifnum\@tempcnta >0 \@whilenum\@tempcnta >0\do
     {\edef\@tempa{\@tempa\the@toks}\advance \@tempcnta \m@ne}%
       \let \@tempb \HH@xexpast \else
```

```
      \let \@tempb \HH@xexnoop \fi
   \def\the@toksz{\the\toks@}\def\the@toks{\the\@temptokena}%
   \edef\@tempa{\@tempa}%
   \expandafter \@tempb \@tempa #4\@@}

\def\HH@xexnoop#1\@@{}
```

\hhline Use a simplified version of `\@mkpream` to break apart the argument to `\hhline`. Actually it is oversimplified, It assumes that the vertical rules are at the end of the column. If you were to specify `c|@{xx}|` in the array argument, then `\hhline` would not be able to access the first vertical rule. (It ought to have an `@` option, and add `\leaders` up to the width of a box containing the `@`-expression. We use a loop made with `\futurelet` rather than `\@tfor` so that we can use `#` to denote the crossing of a double hline with a double vline.
`\if@firstamp` is true in the first column and false otherwise.
`\if@tempswa` is true if the previous entry was a vline (`:`, `|` or `#`).

```
\def\hhline#1{\omit\@firstamptrue\@tempswafalse
```

Put two rules of width `\doublerulesep` in `\box1`

```
\global\setbox\@ne\HH@box\doublerulesep\doublerulesep
```

If Mittelbach's `array.sty` is loaded, we do not need the negative `\hskip`'s around vertical rules.

```
  \xdef\@tempc{\ifx\extrarowheight\HH@undef\hskip-.5\arrayrulewidth\fi}%
```

Now expand the `*`-forms and add dummy tokens (`\relax` and ‘) to either end of the token list. Call `\HH@let` to start processing the token list.

```
    \HH@xexpast\relax#1*0x\@@\toks@{}\expandafter\HH@let\@tempa‘}
```

\HH@let Discard the last token, look at the next one.

```
\def\HH@let#1{\futurelet\@tempb\HH@loop}
```

\HH@loop The main loop. Note we use `\ifx` rather than `\if` in version 2 as the new token `~` is active.

```
\def\HH@loop{%
```

If next token is ‘, stop the loop and put the lines into this row of the alignment.

```
  \ifx\@tempb‘\def\next##1{\the\toks@\cr}\else\let\next\HH@let
```

`|`, add a vertical rule (across either a double or single hline).

```
  \ifx\@tempb|\if@tempswa\HH@add{\hskip\doublerulesep}\fi\@tempswatrue
        \HH@add{\@tempc\vline\@tempc}\else
```

`:`, add a broken vertical rule (across a double hline).

```
  \ifx\@tempb:\if@tempswa\HH@add{\hskip\doublerulesep}\fi\@tempswatrue
     \HH@add{\@tempc\HH@box\arrayrulewidth\arrayrulewidth\@tempc}\else
```

`#`, add a double hline segment between two vlines.

```
  \ifx\@tempb##\if@tempswa\HH@add{\hskip\doublerulesep}\fi\@tempswatrue
       \HH@add{\@tempc\vline\@tempc\copy\@ne\@tempc\vline\@tempc}\else
```

`~`, A column with no hline (this gives an effect similar to `\cline`).

```
  \ifx\@tempb~\@tempswafalse
        \if@firstamp\@firstampfalse\else\HH@add{&\omit}\fi
           \HH@add{\hfil}\else
```

`-`, add a single hline across the column.

```
\ifx\@tempb-\@tempswafalse
          \if@firstamp\@firstampfalse\else\HH@add{&\omit}\fi
             \HH@add{\leaders\hrule\@height\arrayrulewidth\hfil}\else
```

`=`, add a double hline across the column.

```
\ifx\@tempb=\@tempswafalse
     \if@firstamp\@firstampfalse\else\HH@add{&\omit}\fi
```

Put in as many copies of `\box1` as possible with `\leaders`, this may leave gaps at the ends, so put an extra box at each end, overlapping the `\leaders`.

```
      \HH@add
         {\rlap{\copy\@ne}\leaders\copy\@ne\hfil\llap{\copy\@ne}}\else
```

`t`, add the top half of a double hline segment, in a `\rlap` so that it may be used with `b`.

```
\ifx\@tempb t\HH@add{\rlap{\HH@box\doublerulesep\z@}}\else
```

`b`, add the bottom half of a double hline segment in a `\rlap` so that it may be used with `t`.

```
\ifx\@tempb b\HH@add{\rlap{\HH@box\z@\doublerulesep}}\else
```

Otherwise ignore the token, with a warning.

```
\PackageWarning{hhline}%
    {\meaning\@tempb\space ignored in \noexpand\hhline argument%
     \MessageBreak}%
\fi\fi\fi\fi\fi\fi\fi\fi\fi
```

Go around the loop again.

```
\next}
```

⟨/package⟩